

PunyInform

## **PunyInform**

*An Inform library for writing small and fast text adventures.*

Version 1.7, 4 November 2020

PunyInform was conceived and designed by Johan Berntsson and Fredrik Ramsberg. Coding by Johan Berntsson, Fredrik Ramsberg, Pablo Martinez and Tomas Öberg. Includes code from the Inform 6 standard library, by Graham Nelson. Thanks to Stefan Vogt, Jason Compton, John Wilson, Hugo Labrande and Richard Fairweather for advice, testing, code contributions and promotion. Thanks to David Kinder and Andrew Plotkin for helping out with compiler issues and sharing their deep knowledge of the compiler. Huge thanks to Graham Nelson for creating the Inform 6 compiler and library in the first place.

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
<b>2</b>	<b>Comparison with the Inform 6 Standard Library</b>	<b>5</b>
	Getting Started . . . . .	5
	Actions . . . . .	6
	The basic actions . . . . .	6
	OPTIONAL_EXTENDED_VERBSET actions . . . . .	6
	OPTIONAL_EXTENDED_METAVERBS actions . . . . .	7
	DEBUG actions . . . . .	7
	Articles . . . . .	7
	Plural . . . . .	7
	Daemons and Timers . . . . .	8
	Time-based Games . . . . .	8
	Library Messages and Customization . . . . .	8
	Printing the Contents of an Object . . . . .	9
	Direction Handling . . . . .	10
	Fake direction objects. . . . .	11
	Disabling directions . . . . .	11
	Ship directions . . . . .	11
	Look . . . . .	11
	Scoring . . . . .	12
	Box Statements and Menus . . . . .	12
	Scope . . . . .	13
	Manual Scope . . . . .	13
	Parser . . . . .	14
<b>3</b>	<b>Programming Advice</b>	<b>15</b>
	Error messages . . . . .	15
	Debugging . . . . .	15
	Customizing the Library . . . . .	16
	Optionals . . . . .	16
	Parameters . . . . .	17
	Abbreviations . . . . .	18
	Limitations for z3 . . . . .	18

Properties . . . . .	19
<b>4 Extensions</b>	<b>20</b>
flags . . . . .	20
cheap_scenery . . . . .	21
quote_box . . . . .	22
menu . . . . .	23
Extract from DM3 . . . . .	23
<b>5 Appendix A: List of Routines</b>	<b>25</b>
Library Routines . . . . .	25
Entry Point Routines . . . . .	26
Additional Public Routines . . . . .	27
PunyInform Public Routines . . . . .	27
<b>6 Appendix B: List of Properties</b>	<b>28</b>
<b>7 Appendix C: List of Attributes</b>	<b>30</b>
<b>8 Appendix D: List of Variables</b>	<b>32</b>
<b>9 Appendix E: List of Constants</b>	<b>34</b>
<b>10 Appendix F: Grammar</b>	<b>36</b>

# Chapter 1

## Introduction

PunyInform is a library written in Inform 6 which allows people to create text adventures/interactive fiction using the Z-machine virtual machine.

The main goal of PunyInform is to allow for games which are fast and have a small memory footprint. This should make the games run well on older architectures, such as the 8 bit computers of the 1980s. Our main target is to make it suitable for games on the Commodore 64 using Ozmoos (<https://github.com/johanberntsson/ozmoos>)

PunyInform is based on the Inform 6 standard library, developed by Graham Nelson. In this document DM4 refers to the *Inform Designer's Manual, 4th edition*, which is available online at: <http://www.inform-fiction.org/manual/html/index.html>

A PunyInform game can be compiled to Z-code version 3, 5 or 8 (z3, z5 or z8), but not Glulx. To compile games using PunyInform, you need the official Inform compiler maintained by David Kinder, at <https://github.com/DavidKinder/Inform6>. Binaries can be found at if-archive. Please note that PunyInform uses features that were introduced in Inform v6.34 and using earlier versions of the compiler will cause errors.

## Chapter 2

# Comparison with the Inform 6 Standard Library

A game written in PunyInform is very similar to a game written with the Inform 6 standard library. However, there are some major differences that are documented in this section.

### Getting Started

To compile a game, unpack the files, place the Inform 6.34 compiler binary (Get the source or an executable at <http://www.ifarchive.org/indexes/ifarchiveXinfocomXcompilersXinform6.html>) in the base directory, and type i.e. `inform6 +lib -v3 -s -e library_of_horror.inf` (type `inform6 -h2` for an explanation of all commandline switches).

You can use the `minimal.inf` file, supplied with PunyInform, as a starting point for developing a new game.

The general pattern of a PunyInform game is:

```
Constant INITIAL_LOCATION_VALUE = ...;

! define library constants here

Include "globals.h";

! define your own global variables here

! add extension routines and other library customizations here

Include "puny.h";
```

```

! add normal game code here

[Initialise;
  "Welcome to the game!";
];

```

All library constants, including `Story`, `Headline`, `MAX_SCORE`, `OBJECT_SCORE`, `ROOM_SCORE`, `NUMBER_TASKS`, `TASKS_PROVIDED`, `AMUSING_PROVIDED`, `MAX_CARRIED` and `SACK_OBJECT` should be defined before including `globals.h`, if needed. The roles of these constants are documented in `DM4`.

Library customization, such as supplying a library extension point like `PrintTask`, goes between the `globals.h` and `puny.h` inclusions.

After the includes you add game code and an `Initialise` routine, as in other Inform games.

## Actions

PunyInform has most of the actions that the standard library has, but they are divided into four sets. The basic set of actions is part of the core library. Then there is a set of normal actions which can be enabled by defining the constant `OPTIONAL_EXTENDED_VERBSET` and a set of meta actions which can be enabled by defining `OPTIONAL_EXTENDED_METAVERBS`. Finally, just as in the standard library, there is a set of debug verbs, which can be enabled by defining the symbol `DEBUG`.

### The basic actions

Normal actions: `Answer`, `Ask`, `AskTo`, `AskFor`, `Attack`, `Close`, `Consult`, `Cut`, `Dig`, `Disrobe`, `Drink`, `Drop`, `Eat`, `Enter`, `Examine`, `Exit`, `Fill`, `GetOff`, `Give`, `Go`, `Inv`, `Insert`, `Jump`, `JumpOver`, `Listen`, `Lock`, `Look`, `Open`, `Pull`, `Push`, `PushDir`, `PutOn`, `Remove`, `Rub`, `Search`, `Show`, `Smell`, `SwitchOff`, `SwitchOn`, `Take`, `Tie`, `Tell`, `ThrowAt`, `Touch`, `Transfer`, `Turn`, `Unlock`, `Wait`, `Wear`.

Meta actions: `Again`, `FullScore`, `LookModeNormal`, `LookModeLong`, `LookModeShort`, `NotifyOn`, `NotifyOff`, `Oops`, `OopsCorrection`, `Quit`, `Restart`, `Restore`, `Save`, `Score`, `Version`.

### OPTIONAL\_EXTENDED\_VERBSET actions

Normal actions: `Blow`, `Burn`, `Buy`, `Empty`, `EmptyT`, `GoIn`, `Kiss`, `Mild`, `No`, `Pray`, `Set`, `SetTo`, `Sing`, `Sleep`, `Sorry`, `Strong`, `Squeeze`, `Swim`, `Swing`, `Taste`, `Think`, `Wake`, `WakeOther`, `Wave`, `WaveHands`, `Yes`.

## OPTIONAL\_EXTENDED\_METAVERBS actions

Meta actions: CommandsOn, CommandsOff, CommandsRead, Places, Objects, ScriptOn, ScriptOff, Verify.

Note: Places and Objects can be disabled by defining the constant NO\_PLACES.

## DEBUG actions

Meta actions: ActionsOn, ActionsOff, GoNear, Pronouns, Purloin, RandomSeed, RoutinesOn, RoutinesOff, Scope, TimersOn, TimersOff, Tree.

## Articles

PunyInform, unlike the Inform standard library, will not figure out when an object should have the indefinite article “an”. You need to specify it using the `article` property every time it should be “an”. Example:

```
Object Umbrella "umbrella"
  with
    name 'umbrella',
    article "an";
```

Another difference is that PunyInform doesn't support the `articles` (note the `s`) property. This was only added to the Inform library because it's useful for some languages other than English.

## Plural

PunyInform can handle a collection of objects as long as they can be described with full names, but it does not offer support for indistinguishable objects. The library supports `pluralname` and the plural marking on dictionary words with the `//p` suffix.

For example

```
Object -> RedBook "red book"
  with name 'red' 'book' 'books//p';
```

```
Object -> BlueBook "blue book"
  with name 'blue' 'book' 'books//p';
```

can be used like

```
> take book
Do you mean the red book, or the blue book? > red
```

Taken.

```
> drop book
Dropped.
```

```
> take all books
red book: Taken.
blue book: Taken.
```

## Daemons and Timers

Property `daemon` is an alias for property `time_out`. This means you can't have a daemon and a timer on the same object. If you want both, put one of them in another object, possibly a dummy object whose only purpose is to hold the timer/daemon.

## Time-based Games

PunyInform supports time-based games as described in DM4. To show time in the status line, put `Statusline time;` in the beginning of the source, and add a call to `SetTime` in the `initialise` routine.

```
Statusline time;
Include "globals.h";
Include "puny.h";
[Initialise;
    SetTime(1 * 60 + 5, 5); ! 1:05 am, each turn 5 minutes
];
```

## Library Messages and Customization

All system messages that can be replaced can be found in the file `messages.h`.

PunyInform uses two form of library messages: static strings and complex messages. A typical static string is `"Taken."`. If a message has parts that vary, if the same message should be shared by several different message identifiers, or a newline should NOT be printed after the message, the message needs to be a complex message. A complex message has its own piece of code to print it.

Each message is defined as either a static string or a complex message in `messages.h`. If you want to replace a message, you can choose to replace it with a static string or a complex message, regardless of its type in `messages.h`. You do this by defining constants and possibly a `LibraryMessages` routine before the inclusion of `puny.h`.

To replace a message with a static string, define a constant with the same name as the message identifier and give it a string value, i.e:

```
Constant MSG_INSERT_NO_ROOM "It's kinda full already, I'm afraid.";
```

To replace a message with a complex message, define a constant with the same name as the message identifier, give it a value in the range 1000-1299 and provide a LibraryMessages routine to handle it, i.e:

```
Constant MSG_EXAMINE_NOTHING_SPECIAL 1000;
```

```
[LibraryMessages p_msg p_arg_1 p_arg_2;  
  switch(p_msg) {  
    MSG_EXAMINE_NOTHING_SPECIAL:  
      print_ret (The) noun, " looks perfectly normal in every way."  
    }  
  rfalse;  
];
```

The LibraryMessages routine takes three arguments - a message identifier (p\_msg) and two optional arguments (p\_arg\_1 and p\_arg\_2) which a few messages use. The return value of this routine is unimportant.

IMPORTANT: If you have defined a constant to replace a certain error message with a complex message, you *have to* print something for this message.

## Printing the Contents of an Object

The standard library provides the routine WriteListFrom(). PunyInform provides PrintContents() instead. While not quite as versatile as WriteListFrom, it's meant to be easy to use, easy to remember how to use, and powerful enough to cover the needs for most situations. This is how it works:

```
PrintContents(p_first_text, p_obj, p_check_workflag);  
Print what's in/on p_obj recursively.
```

p\_first\_text:

A string containing a message to be printed before printing the first item in/on p\_obj. Can also be 0 to not print a text, or a routine, which will then be called with p\_obj as an argument.

p\_obj:

The container/supporter/person whose contents we want to list.

p\_check\_workflag:

If true, only list objects which have the workflag set (this rule only applies on the top level.

Return value:

true if any items were printed, false if not.

Typical usage:

```
if(PrintContents("On the table you can see ", OakTable)) print ".";
```

## Direction Handling

The Compass and the twelve direction objects, as described in DM4, are not available in PunnyInform. Instead, there is a single object called `Directions` and two global variables called `selected_direction` and `selected_direction_index`. This helps in keeping the object count down, considering that a z3 game can have no more than 255 objects.

Whenever the player has typed a direction, `noun` is `Directions` and `selected_direction` contains the property number for the direction the player typed. If the player didn't type a direction, `selected_direction` is 0. The name of the Direction object is always the currently selected direction, or "direction" if no direction is selected. So, to implement a robot which will stop the player from going north or east, one might write a `react_before` routine like this:

```
Object Robot "Floyd"
  with
    react_before [;
      Go:
        if(selected_direction == n_to or e_to)
          "~My mother always told me to avoid going ",
          (name) Directions, ".~, says Floyd.";
    ],
  has animate;
```

`selected_direction_index` can be used to look up the dictionary words which refer to that direction, the property number and the name of the direction:

```
! prints the short dictionary word, like 'n/'
print (address) abbr_direction_array-->selected_direction_index;
! prints the long dictionary word, like 'north'
print (address) full_direction_array-->selected_direction_index;
! prints the property number, like 7
print direction_properties_array-->selected_direction_index;
! prints the direction name, like "north"
print (string) direction_name_array-->selected_direction_index;
```

Each of these arrays is a table, so all of them have the number of directions as element 0. The number of directions is also held in the constant `DIRECTION_COUNT`. This is useful if you're writing a library extension and want to iterate over all directions in a safe manner. Please note that the directions are stored in element 1 .. `DIRECTION_COUNT` in these arrays.

## Fake direction objects.

For each direction, there is also a fake direction object: `FAKE_N_OBJ`, `FAKE_SW_OBJ`, `FAKE_OUT_OBJ` etc. If you need to generate an action in code which has a direction in it, this requires using the corresponding fake direction object, like this:

```
<<Go FAKE_N_OBJ>>;
<<Push Stone FAKE_NW_OBJ>>;
```

If you want to go in a direction and you know the property number for that direction, you can find the corresponding fake direction object by calling `DirPropToFakeObj()`:

```
dir_prop = ne_to; ! Or any direction you like
fake_obj = DirPropToFakeObj(dir_prop);
<<Go fake_obj>>;
```

There is also an inverse of this function, called `FakeObjToDirProp()`, which may come in handy in some situations.

Each fake direction object is just a constant. `PunyInform` recognizes these constants and sets `selected_direction` and `selected_direction_index` properly. As far as we can tell, the only use for the fake direction objects is in actions in code as outlined above.

## Disabling directions

If you (perhaps temporarily) don't want the game to recognize any directions, you can set the global variable `normal_directions_enabled` to false.

## Ship directions

If you define the constant `OPTIONAL_SHIP_DIRECTIONS`, the parser will recognize 'fore' and 'f' as synonyms for north, 'aft' and 'a' as synonyms for south, 'port' and 'p' as synonyms for west, and 'starboard' and 'sb' as synonyms for east.

If you (temporarily) don't want the game to recognize ship directions, you can set the global variable `ship_directions_enabled` to false.

## Look

`PunyInform`, unlike the standard library, doesn't support using the `describe` property for room descriptions. The `description` property works, of course.

When deciding how to show objects, these are the rules that apply in `PunyInform`:

- If the object provides `describe`, print or run it. If it's a string, or it's a routine and it returns true, the object will not be described any further.

Note that this string or routine should start by printing a newline, unless it's a routine which decides not to print anything at all.

- We will now figure out which the current description property of the object is:
  - If the object is a container or a door, it's `when_open` or `when_closed`, depending on its state.
  - If the object is a switchable object, it's `when_on` or `when_off`, depending on its state.
  - Otherwise, it's `initial`.
- If the object provides this property AND the object hasn't moved or the property is `when_off` or `when_closed`, then print a newline and run or print the string or routine held in the property.
- If, according to the above rules, nothing has yet been printed, include the object in the list of objects printed at the end.

Note: Thanks to aliasing, PunyInform uses only 28 common properties, which is 20 less than the Inform 6 library. This is necessary to support compiling to z3. However, this also means the library can't tell if an object provides `initial`, `when_on` or `when_open` - these are in fact all aliases for the same property. For this reason, the printing rules described above must be a little restrictive. In fact, the Inform Designer's Manual, 4th ed. describes rules which are equally restrictive, since Inform 6 used aliasing as well when the DM4 was released, but newer versions of the Inform 6 library are actually smarter than the DM4 says and will look at which properties are provided and act accordingly. For PunyInform, whenever you have problems getting the results you want using `when_on`, `when_open` etc, write the logic you like in a `describe` routine instead. That way you can make it work exactly the way you want.

## Scoring

Scoring works as in DM4, but it is divided into basic scoring using the `score` and `MAX_SCORE` variables, and extended scoring which is enabled by defining the `OPTIONAL_FULL_SCORE` global in the game. When `OPTIONAL_FULL_SCORE` is defined, then full scoring is available, with the "full score" command, tasks as described in DM4, and the `scored` attribute for scoring objects and locations in the game using the `OBJECT_SCORE` and `ROOM_SCORE` constants.

## Box Statements and Menus

The box statement is not available in version 3 games, and the usual menu extensions will not work either since version 3 games lack cursor control commands. Instead PunyInform provides an extension that approximates this functionality. See the Extensions section for more detail.

## Scope

Scope in PunyInform is a list of things you can interact with. This includes things you can see in the room description, but can also include abstract concepts such as directions and discussion topics. Two library routines enable you to see what's in scope and what isn't. The first, `TestScope(obj, actor)`, simply returns true or false according to whether or not `obj` is in scope. The second is `LoopOverScope(routine, actor)` and calls the given routine for each object in scope. In each case the `actor` given is optional, and if it's omitted, scope is worked out for the player as usual.

The routines `ScopeCeiling`, `LoopOverScope`, `ScopeWithin` and `TestScope` are implemented as described in DM4. Two routines are used to determine if you can touch or see an object: `ObjectIsUntouchable(obj, flag)` and `ObjectIsInvisible(obj, flag)`. Both functions return true if the `obj` is untouchable or invisible from the player's point of view. If `flag` is true, then the routine never writes anything and only returns true or false to say if the `obj` was untouchable/invisible or not. If `flag` is false, the routine will also write messages like "You can't because ... is in the way." when a problem was found.

The standard Inform parser uses a number of internal scope variables that are not used in PunyInform, including `scope_reason`. Code that relies on these variables has to be rewritten. However, `scope_stage` is supported and is used when the scope token is used, so constructs like the code fragment below work as described in DM4.

```
Object questions "questions";
Object -> "apollo"
  with name 'apollo',
       description "Apollo is a Greek god.";

[ QueryTopic;
  switch (scope_stage) {
    1: rfalse;
    2: ScopeWithin(questions); rtrue;
    3: "At the moment, even the simplest questions confuse you.";
  }
];

[ QuerySub; noun.description();];
Verb 'what' * 'is'/'was' scope=QueryTopic -> Query;
```

## Manual Scope

Normally, PunyInform updates the scope when a turn starts, before the after routines are run, before the timers and daemons are run, and before each `_turn` is run. To get the best possible performance, you can switch to manual scope

updates. You do this by defining the constant `OPTIONAL_MANUAL_SCOPE`. With manual scope enabled, scope is only updated at the start of each turn AND when the program signals that an update may be needed. You signal this by setting the variable `scope_modified` to `true`. A simple rule is to do this anytime you use `move` or `remove` or you alter any of the attributes `open`, `transparent`, `light`. This is already in place in the `PlayerTo` routine as well as in the action routines for `Open`, `Close`, `Take`, `Drop` etc. Sample usage:

```
Object Teleporter "teleporter"
  with
    name 'teleporter',
    capacity 1,
    before [ c;
      SwitchOn:
        c = child(self);
        if(c ~= 0) {
          move c to SecretChamber;
          scope_modified = true;
          print_ret (The) c, " disappears!";
        }
    ],
  has container openable transparent;
```

## Parser

The parser is to a large extent compatible with Inform, for example `wn`, `NextWord()` and `NextWordStopped()` are implemented, and `noun/second/inp1/inp2/special_number/parsed_number` work the same.

General parse routines are supported with the exception of `GRP_REPARSE` which isn't supported. The reason for this is that version 3 games cannot retokenise the input from the reconstructed string.

## Chapter 3

# Programming Advice

### Error messages

The Inform standard veneer routine for printing informative messages for all sorts of runtime errors that can occur is replaced with a simpler routine in PunyInform, saving about 1.5 KB. However, the original routine is used if the constant `RUNTIME_ERRORS` is set to 2.

### Debugging

By defining the constant `DEBUG` (or adding `-D` to the inform 6 compiler commandline), the game is compiled in debug mode. This means a number of meta verbs are available for inspecting the game world and examining which routines and actions are executed. These are the debug verbs supplied:

*TREE* : Show the object tree for the current location. *TREE [object]* : Show the object tree for this object.

*GONEAR [object]* : Teleport to the location of the object.

*SCOPE [actor]* : List the objects which are currently in scope for the actor. Actor defaults to player.

*PRONOUNS* : List what he, she, it and them are currently referring to.

*RANDOM [number]* : Seed the pseudo-random number generator, to make randomization predictable. Number defaults to 100.

*PURLOIN [object]* : Teleport the object into your inventory, no matter where it is.

*ROUTINES [on/off]* : Show which routines are being executed.

*ACTIONS* [on/off] : Show which actions are being invoked.

*TIMERS* [on/off] : Show which timers and daemons are being executed.

Please note: Debug mode uses some convenient features of the Z-machine which are not supported on all of the old Z-code interpreters which Infocom made. Please do your debugging on modern interpreters like Frotz, Bocfel, Ozmo etc. After all Debug mode is meant for debugging your Inform code, not for debugging Z-code interpreters.

## Customizing the Library

PunyInform is designed to be as small as possible to run well on old computers, and some features that add to the size have been made optional. If you want to enable these features, add a line like “Constant OPTIONAL\_GUESS\_MISSING\_NOUN;” before including globals.h, but keep in mind that it will make the game larger. You can also change some parameters in the library from their default values to further adjust the library size as needed. Finally you can use abbreviations to reduce the game size further. PunyInform includes a set of standard abbreviations which can be enabled as needed.

These customizations are described in detail in the following sections.

## Optionals

The optional parts of PunyLib can be enabled with these constants:

Option	Size	Comment
DEBUG	1814 bytes	enable some debugging verbs for game development. These include ‘scope’, ‘random’, ‘pronouns’, ‘tree’, ‘purloin’, ‘gonear’, ‘routines’, ‘actions’ and ‘timers’/‘daemons’.
OPTIONAL_ALLOW_ WRITTEN_NUMBERS	300 bytes	to be able to parse “one”, “two” etc as numbers.
OPTIONAL_ EXTENDED_ METAVERBS	940 bytes	add a set of less important, but nice to have, meta verbs to the grammar.
OPTIONAL_ EXTENDED_ VERBSET	2152 bytes	add a set of less important, but nice to have, verbs to the grammar.

<b>Option</b>	<b>Size</b>	<b>Comment</b>
OPTIONAL_FULL_DIRECTIONS	112 bytes	Include directions NW, SW, NE and SE. Including them also makes the parsing process slightly slower in z3 mode, and uses one more common property.
OPTIONAL_FULL_SCORE	454 bytes	adds the fullscore verb, and support for tasks and the scored attribute as described in DM4.
OPTIONAL_GUESS_MISSING_NOUN	290 bytes	add code to guess missing parts of an incomplete input, such as a door when typing only 'open', and accepting the input with a "(assuming the wooden door)" message.
OPTIONAL_MANUAL_SCOPE	12 bytes	let the game code say when scope needs to be updated, for better performance. See Manual Scope for instructions on how to use it.

## Parameters

The parameters listed in the table below can be adjusted in a game by redefining them before `globals.h` is included.

<b>Parameter</b>	<b>Default</b>	<b>Comment</b>
MAX_CARRIED	32	the max number of items the user can carry at once
MAX_WHICH_OBJECTS	10	max number to include in a "which X do you mean?" parser question
MAX_MULTIPLE_OBJECTS	32	max number of objects that match "all" in an input such as "get all"
MAX_INPUT_CHARS	78	max number of characters in one line of input from the player
MAX_INPUT_WORDS	20	max number of words in a parsed sentence
MAX_FLOATING_OBJECTS	32	max number of floating objects
MAX_SCOPE	32	max number of objects to consider when calculating the scope of the player

Parameter	Default	Comment
RUNTIME_ERRORS	1 or 2	Runtime error reporting: 0 = minimum, 1 = report all errors using error codes, 2 = report all errors using error messages. Default is 2 in DEBUG mode, and 1 when not in DEBUG mode.

## Abbreviations

PunyInform can use a set of standard abbreviations to make strings more compact. If you want to provide your own abbreviations, define the constant `CUSTOM_ABBREVIATIONS` in your game. Keep in mind that you need to compile with the “-e” flag to make the compiler use abbreviations.

## Limitations for z3

If you want to compile a game to z3 format, this is what you need to keep in mind:

- A game can use no more than 30 common properties. PunyInform defines 27 common properties (28 if `OPTIONAL_FULL_DIRECTIONS` is defined).
- A game can use no more than 32 attributes. PunyInform defines 28 attributes (29 if `OPTIONAL_FULL_SCORE` is defined).
- Arrays in common properties can only hold four values. Arrays in individual properties however, can hold 32 values.
- When using message passing (like “`MyBox.AddWeight(5)`”), no more than one argument may be passed. (In regular Inform, message passing doesn’t work at all in z3.)
- Dynamic object creation and deletion can not be used.
- If you need more than four names for an object in a z3 game, give it a `parse_name` routine.
- The room name printed on the statusline is always the object name string. It can’t be overridden with `short_name` in a class or in the same object. Read below for a possible workaround.

**IMPORTANT:** Currently, there is a bug in the compiler which corrupts objects which have common property arrays of length  $> 4$  in z3 games.

When the player is inside an object, in a z5 game, the library will print the name of the object on the statusline, in definite form (“The box”). In a z3 game, the object name string will be printed as-is, typically like “box”. This behavior in z3 games is part of the Z-machine specification so it’s nothing that the game or the library can change. If you want a z3 game to print a different name for when

the player is inside the object, you can set the object name string to the desired name, and override it with `short_name` for all other uses, like this:

```
Object box "The box"  
  with short_name "box"  
  has container openable enterable;
```

## Properties

A property can be used to store a 16-bit value, or an array of values. In z5, a property array can hold up to 32 values. In z3, a property array can only hold 4 values if it is in a common property but 32 values if it is in an individual property.

If a property is declared as additive, the values for an object are concatenated with the values of its class, if any, and put into an array.

A property can either be common or individual. Common properties are a little faster to access and use a little less memory than individual properties. A z5 or z8 game can use a maximum of 62 common properties, while a z3 game can use a maximum of 30 common properties. PunyInform uses 27 common properties, so if you're building a z3 game, you can only add three common properties. If you specify `OPTIONAL_FULL_DIRECTIONS`, PunyInform uses 28 common properties. The value of a common property can always be read, but it can only be written if it has been included in the object declaration. If you don't include it, there is no memory allocated to store a value. If you read the value of such a property, you just get the default value (typically 0).

A common property is created by declaring it with

```
Property propertyname;
```

To access a property, you write `object.__propertyname__`, like this:

```
Dog.description = "The dog looks sleepy.";
```

To check if an object has a value for a property (to see if it can be written if it is a common property or to see if it can be read or written if it is an individual property, use *provides*:

```
If(Dog provides description) ...
```

## Chapter 4

# Extensions

PunyInform keeps the library code size down by only providing the most fundamental functionality by default, but ships with several extensions which can easily be added to games.

### flags

Flags is a mechanism for keeping track of story progression. If you choose to use flags, four procedures with a total size of about 165 bytes are added to the story file. Also, an eight byte array is added to static memory, and one byte is added to dynamic memory for every eight flags. All in all this is a very memory-efficient way of keeping track of progress.

If you want to use flags, after including `globals.h`, set the constant `FLAG_COUNT` to the number of flags you need, and then include `ext_flags.h`.

You then specify a constant for each flag, like this:

```
Constant F_FED_PARROT 0; ! Has the parrot been fed?  
Constant F_TICKET_OK 1; ! Has Hildegard booked her plane tickets?  
Constant F_SAVED_CAT 2; ! Has the player saved the cat in the tree?
```

You get the idea – you give each flag a symbolic name so it’s somewhat obvious what it does. Note that the first flag is flag #0, not flag #1.

Setting a flag on or off means calling the routine `SetFlag(flag#)` or `ClearFlag(flag#)`

To indicate that the player has saved the cat, call `SetFlag(F_SAVED_CAT)`, and to turn off that flag, call `ClearFlag(F_SAVED_CAT)`.

Testing a flag is accomplished by calling `FlagIsSet` or `FlagIsClear`. So if you have a piece of code that should only be run if the parrot has been fed, you would enclose it in an `if(FlagIsSet(F_FED_PARROT)) { ... };` statement.

Naturally, you can test if a flag is clear by calling `FlagIsClear` instead.

## cheap\_scenery

This library extension provides a way to implement simple scenery objects which can only be examined, using just a single object for the entire game. This helps keep both the object count and the dynamic memory usage down. For z3 games, which can only hold a total of 255 objects, this is even more important. To use it, include `ext_cheap_scenery.h` after `globals.h`. Then add a property called `cheap_scenery` to the locations where you want to add cheap scenery objects. You can add up to ten cheap scenery objects to one location in this way. For each scenery object, specify, in this order, one adjective, one noun, and one description string or a routine to print one. Instead of an adjective, you may give a synonym to the noun. If no adjective or synonym is needed, use the value 1 in that position.

Note: If you want to use this library extension in a Z-code version 3 game, you must NOT declare `cheap_scenery` as a common property, or it will only be able to hold one scenery object instead of ten. For z5 and z8, you can declare it as a common property if you like, or let it be an individual property.

If you want to use the same description for a scenery object in several locations, declare a constant to hold that string, and refer to the constant in each location.

Before including this extension, you can also define a string or routine called `SceneryReply`. If you do, it will be used whenever the player does something to a scenery object other than examining it. If it is a string, it is printed. If it is a routine it is called. If the routine prints something, it should return true, otherwise false.

If constant `DEBUG` is defined, the extension will complain about programming mistakes it finds in the `cheap_scenery` data in rooms. Without `DEBUG`, it will keep silent.

Note: If you include this extension, you must either declare `cheap_scenery` as a common property, or use it as an individual property in at least one object, or you will get a compilation error (No such constant as “`cheap_scenery`”).

Example usage:

```
[SceneryReply;
Push:
    "Now how would you do that?";
default:
    rfalse;
```

```

];

Include "ext_cheap_scenery.h";

Constant SCN_WATER = "The water is so beautiful this time of year,
                      all clear and glittering.";

[SCN_SUN;
  deadflag = 1;
  "As you stare right into the sun, you feel a burning sensation
  in your eyes. After a while, all goes black. With no eyesight,
  you have little hope of completing your investigations.";
];

Object RiverBank "River Bank"
  with
    description "The river is quite wide here. The sun reflects
    in the blue water, the birds are flying high up above.",
    cheap_scenery
      'blue' 'water' SCN_WATER
      'bird' 'birds' "They seem so careless."
      1 'sun' SCN_SUN,
  has light;

```

## quote\_box

This is an extension to let games show a simple quote box. For z5+ games, the extension will try to center the quote box on the screen, by reading the screen width reported by the interpreter in the header.

For z3, this information is not available. Instead, it can do it two ways: 1. The game programmer tells the extension to assume the screen has a certain width and the extension uses this information to center the quote box. 2. The game programmer tells the extension to just indent the quote box a fixed number of characters.

To use (1), set the constant QUOTE\_V3\_SCREEN\_WIDTH to the desired width, which has to be > 6.

To use (2), set the constant QUOTE\_V3\_SCREEN\_WIDTH to the desired number of characters to indent by, which must be in the range 0-6.

By default, method (2) will be used, with 2 characters of indentation.

To display a quote box, create a word array holding the number of lines, the number of characters in the longest line, and then a string per line, and call QuoteBox with the array name as the argument.

```

Include "ext_quote_box.h";

Array quote_1 --> 5 35
"When I die, I want to go peacefully"
"in my sleep like my grandfather."
"Not screaming in terror, like the"
"passengers in his car."
"          -- Jack Handey";
!
[AnyRoutine;
  QuoteBox(quote_1);
];

```

## menu

This is an extension to let games show a menu of text options (for instance, when producing instructions which have several topics, or when giving clues). This can be done with the DoMenu routine, which is very similar to the DoMenu in the standard Inform library. In version 3 mode it will create a simple text version instead because of technical limitations.

A common way of using DoMenu is from a “help” verb, which can be declared like so:

```

Include "ext_menu.h";

! add HelpItem, HelpMenu and HelpInfo here

[ HelpSub;
  DoMenu(HelpItems, HelpMenu, HelpInfo);
];

Verb 'help' * -> Help;

```

Below is how DoMenu was described in the *Inform Designer's Manual, 3rd edition*.

### Extract from DM3

Here is a typical call to DoMenu:

```

DoMenu("There is information provided on the following:~
      ~ Instructions for playing
      ~ The history of this game
      ~ Credits~",HelpMenu, HelpInfo);

```

Note the layout, and especially the carriage returns.

The second and third arguments are themselves routines. (Actually the first

argument can also be a routine to print a string instead of the string itself, which might be useful for adaptive hints.) The `HelpMenu` routine is supposed to look at the variable `menu_item`. In the case when this is zero, it should return the number of entries in the menu (3 in the example). In any case it should set `item_name` to the title for the page of information for that item; and `item_width` to half its length in characters (this is used to centre titles on the screen). In the case of item 0, the title should be that for the whole menu.

The second routine, `HelpInfo` above, should simply look at `menu_item` (1 to 3 above) and print the text for that selection. After this returns, normally the game prints “Press [Space] to return to menu” but if the value 2 is returned it doesn’t wait, and if the value 3 is returned it automatically quits the menu as if Q had been pressed. This is useful for juggling submenus about. Menu items can safely launch whole new menus, and it is easy to make a tree of these (which will be needed when it comes to providing hints across any size of game).

## Chapter 5

# Appendix A: List of Routines

PunyInform defines both public and private routines. The private routines are prefixed with an underscore (for example, `_ParsePattern`) and should not be used by a game developer. The public routines do not have this prefix, and are for general use. Most of the public routines work the same, or in a very similar manner, to corresponding routines in DM4, but PunyInform also offers a few extra routines not available in Inform. All public routines are listed below in this section.

### Library Routines

These library routines are supported by PunyInform, as described in DM4.

<b>Library Routine</b>	<b>Comment</b>
Banner	
CommonAncestor	
DrawStatusLine	Not available in version 3 games
IndirectlyContains	
InScope	
LoopOverScope	
NextWord	
NextWordStopped	
NumberWord	
ObjectIsUntouchable	
PlayerTo	
ParseToken	
PlaceInScope	

<b>Library Routine</b>	<b>Comment</b>
PronounNotice	
SetTime	
ScopeWithin	
TestScope	
TryNumber	
WordAddress	
WordLength	
YesOrNo	

## Entry Point Routines

These entry point routines are supported by PunyInform, as described in the DM4.

<b>Entry Point Routine</b>	<b>Comment</b>
AfterLife	
AfterPrompt	
Amusing	
BeforeParsing	
DarkToDark	
DeathMessage	
GamePostRoutine	
GamePreRoutine	
InScope	The et_flag isn't supported.
LookRoutine	
NewRoom	
ParseNumber	
PrintRank	OPTIONAL_FULL_SCORE
PrintTaskName	OPTIONAL_FULL_SCORE
PrintVerb	
TimePasses	
UnknownVerb	

These entry point routines are not supported

<b>Entry Point Routine</b>	<b>Comment</b>
ChooseObjects	The parser internals differ too much
ParseNoun	
ParserError	The parser internals differ too much

## Additional Public Routines

---

<b>Routine Name</b>	<b>Comment</b>
PrintOrRun	
RunRoutines	
CTheyreorThats	Print directive
ItoThem	Print directive
IsOrAre	Print directive

---

## PunyInform Public Routines

---

<b>Routine Name</b>	<b>Comment</b>
OnOff	Print directive
ObjectIsInvisible	Similar to ObjectIsUntouchable (DM4)
PrintContents	
PrintMsg	
RunTimeError	

---

## Chapter 6

# Appendix B: List of Properties

These are the properties defined by the library:

---

**Property**

---

add\_to\_scope  
after  
article  
before  
cant\_go  
capacity  
d\_to  
daemon  
describe  
description  
door\_dir  
door\_to  
each\_turn  
e\_to  
found\_in  
in\_to  
initial  
inside\_description  
invent  
life  
n\_to  
name  
ne\_to

---

<b>Property</b>
number
nw_to
orders
out_to
parse_name
react_after
react_before
s_to
se_to
short_name
sw_to
time_left
time_out
u_to
w_to
when_closed
when_off
when_on
when_open
with_key

---

The properties articles, grammar, list\_together, plural and short\_name\_indef, which are supported by the Inform 6 library, are not supported by PunyInform.

The with\_key property can also hold a routine. The routine should return false or the object id of the key that fits the lock. When this routine is called, **second** holds the object currently being considered as a key. This can be used to allow multiple keys fit a lock.

## Chapter 7

# Appendix C: List of Attributes

These attributes are the same as in DM4.

---

**Attribute**

---

absent  
animate  
clothing  
concealed  
container  
door  
edible  
enterable  
female  
general  
light  
lockable  
locked  
moved  
neuter  
on  
open  
openable  
pluralname  
proper  
scenery  
static  
supporter  
switchable

---

**Attribute**

---

talkable  
transparent  
visited  
workflag  
worn

---

These attributes are used in the Inform standard library and are listed in DM4, but are not used in PunyInform.

---

<b>Attribute</b>	<b>Comment</b>
male	not needed, assumed if an object is animate and it is not female or neuter

---

## Chapter 8

# Appendix D: List of Variables

These variables are the same as in DM4.

---

**Variable**

---

action  
actor  
consult\_from  
consult\_words  
deadflag  
herobj  
himobj  
inp1  
inp2  
inventory\_stage  
itobj  
keep\_silent  
location  
lookmode  
num\_words  
parsed\_number  
parser\_action  
real\_location  
scope\_stage  
score  
second  
special\_number  
verb\_word  
verb\_wordnum

---

**Variable**

---

wn

---

These variables are PunyInform only.

---

**Variable**

---

These variables are used in the Inform standard library and are listed in DM4, but are not used in PunyInform.

---

**Variable**

---

c\_style  
et\_flag  
listing\_together  
lm\_n  
lm\_o  
notify\_mode  
parser\_one  
parser\_two  
scope\_reason  
standard\_interpreter  
the\_time  
vague\_object

---

## Chapter 9

# Appendix E: List of Constants

These constants are the same as in DM4.

---

Constant Name
AMUSING_PROVIDED
GPR_FAIL
GPR_MULTIPLE
GPR_NUMBER
GPR_PREPOSITION
GPR_REPARSE
Headline
MAX_CARRIED
MAX_SCORE
MAX_TIMERS
NUMBER_TASKS
OBJECT_SCORE
ROOM_SCORE
SACK_OBJECT
Story
TASKS_PROVIDED

---

These constants are used in the Inform standard library and are listed in DM4, but are not used in PunyInform. Most of them are parser specific for the standard lib, and the PunyInform parser works differently.

---

**Constant Name**

---

ANIMA\_PE  
ASKSCOPE\_PE  
CANTSEE\_PE  
DEATH\_MENTION\_UNDO  
EACHTURN\_REASON  
ELEMENTARY\_TT  
EXCEPT\_PE  
ITGONE\_PE  
JUNKAFTER\_PE  
LOOPOVERSCOPE\_REASON  
MMULTI\_PE  
MULTI\_PE  
NO\_PLACES  
NOTHELD\_PE  
NOTHING\_PE  
NUMBER\_PE  
PARSING\_REASON  
REACT\_AFTER\_REASON  
REACT\_BEFORE\_REASON  
SCENERY\_PE  
SCOPE\_TT  
STUCK\_PE  
TALKING\_REASON  
TESTSCOPE\_REASON  
TOOFEW\_PE  
TOOLIT\_PE  
UPTO\_PE  
USE\_MODULES  
VAGUE\_PE  
VERB\_PE

---

## Chapter 10

# Appendix F: Grammar

Here are the standard verbs defined in the library.

---

### Verbs

---

answer say shout speak  
ask  
attack break crack destroy  
climb scale  
close cover shut  
cut chop prune slice  
dig  
drink sip swallow  
drop discard throw  
eat  
enter cross  
examine x  
exit out outside  
fill  
get  
give feed offer pay  
go run walk  
insert  
inventory inv i  
jump hop skip  
leave  
listen hear  
lock  
look l  
open uncover unwrap  
pick

---

<b>Verbs</b>
pull drag
push clear move press shift
put
read
remove
rub clean dust polish scrub
search
shed disrobe doff
show display present
sit lie
smell sniff
stand
switch
take carry hold
tell
tie attach fasten fix
touch feel fondle grope
turn rotate screw twist unscrew
unlock
wait z
wear don

---

This set of extended verbs are not included by default, but can be added by defining OPTIONAL\_EXTENDED\_VERBSET.

<b>Verbs</b>	<b>Comment</b>
blow	OPTIONAL_EXTENDED_VERBSET
bother curses darn drat	OPTIONAL_EXTENDED_VERBSET
burn light	OPTIONAL_EXTENDED_VERBSET
buy purchase	OPTIONAL_EXTENDED_VERBSET
consult	OPTIONAL_EXTENDED_VERBSET
empty	OPTIONAL_EXTENDED_VERBSET
in inside	OPTIONAL_EXTENDED_VERBSET
kiss embrace hug	OPTIONAL_EXTENDED_VERBSET
no	OPTIONAL_EXTENDED_VERBSET
peel	OPTIONAL_EXTENDED_VERBSET
pray	OPTIONAL_EXTENDED_VERBSET
pry prise prize lever jemmy force	OPTIONAL_EXTENDED_VERBSET
set adjust	OPTIONAL_EXTENDED_VERBSET
shit damn fuck sod	OPTIONAL_EXTENDED_VERBSET
sing	OPTIONAL_EXTENDED_VERBSET
sleep nap	OPTIONAL_EXTENDED_VERBSET
sorry	OPTIONAL_EXTENDED_VERBSET

<b>Verbs</b>	<b>Comment</b>
squeeze squash	OPTIONAL_EXTENDED_VERBSET
swim dive	OPTIONAL_EXTENDED_VERBSET
swing	OPTIONAL_EXTENDED_VERBSET
taste	OPTIONAL_EXTENDED_VERBSET
think	OPTIONAL_EXTENDED_VERBSET
transfer	OPTIONAL_EXTENDED_VERBSET
wake awake awaken	OPTIONAL_EXTENDED_VERBSET
wave	OPTIONAL_EXTENDED_VERBSET
yes y	OPTIONAL_EXTENDED_VERBSET

This set of PunyInform debug verbs are not included by default, but can be added by defining DEBUG.

<b>Verbs</b>	<b>Comment</b>
actions	DEBUG
gonear	DEBUG
pronouns nouns	DEBUG
purloin	DEBUG
random	DEBUG
routines messages	DEBUG
scope	DEBUG
timers daemons	DEBUG
tree	DEBUG

These debug verbs defined in the library are not supported by PunyInform.

<b>Verbs</b>	<b>Comment</b>
abstract	not in PunyInform
changes	not in PunyInform
goto	not in PunyInform
showobj	not in PunyInform
showverb	not in PunyInform
trace	not in PunyInform

These are the meta verbs. Some are only included when OPTIONAL\_EXTENDED\_METAVERBS is defined, and some are not defined if NO\_PLACES is defined.

<b>Verbs</b>	<b>Comment</b>
brief normal	
fullscore full	

---

<b>Verbs</b>	<b>Comment</b>
noscript unscript	OPTIONAL_EXTENDED_METAVERBS
notify	
objects	OPTIONAL_EXTENDED_METAVERBS and not NO_PLACES
places	OPTIONAL_EXTENDED_METAVERBS and not NO_PLACES
quit q die	
recording	OPTIONAL_EXTENDED_METAVERBS
replay	OPTIONAL_EXTENDED_METAVERBS
restart	
restore	
save	
score	
script transcript	OPTIONAL_EXTENDED_METAVERBS
superbrief short	
verify	OPTIONAL_EXTENDED_METAVERBS
verbose long	
version	

---